



2CH GSM DOOR OPENING CONTROLLER



TMT Global 2 channel GSM Gate Opener

Features

- Free charges. the call from authorized number then carry's out the turn ON/OFF
- Control 2 devices(Gates, bollards, barriers, garage doors, shutters and access doors or machines
- Secure - Using caller ID for identification, unknown callers are ignored
- Can be operated from anywhere, no distance limit
- Call in to be users in 30 mins when the storage mode start ,R admin send SMS to add/remove the users.
- Up to 1000 authorized phone numbers can be configured
- Two Digital inputs for door sensor
- motion sensors or other sensors to protect your door and windows,
- when any one of them triggered, will send SMS alert message to admin immediately;
- 2 relay output, 4 output mode
- The relay action will return a SMS confirmation to the owner
- Based on GSM Network, R applications.
- Wired connection function when the wired interface is in
- low level , the relay will be forced to turn off.

Technical Parameters	
SIM Card	Supporting 1.8/3V SIM Card
Parameter Item	Reference scope
Antenna	50 Ω SMA Antenna interface
DC Power Supply	9~24VDC 2A
Temperature	-20~+60 °C
Power Consumption	12V input, Max. 50mA/Average 50mA
Humidity	Relative humidity 90% (condensation free)
Frequency	Quad band 850/900/1800/1900Mhz(Optional)
Relay Output	2, Dry Contact, NC or NO, 2A/30V DC

ORDERING INFORMATION	
MODEL NO	DESCRIPTION
TMT-7752	2CH GSM DOOR OPENING CONTROLLER