

AHD Auto Focus Varifocal Fixed IR Bullet Camera





**TMT GLOBAL 2,3,4,5,4K/8 MP Auto Focus motorized lens
2.8-12mm Auto focus AHD Bullet Camera**

Features

- Waterproof Bullet Camera
- 3-axis Adjustable Bracket
- Lens: Auto focus Varifocal 2.8-12mm
- Adjustable Zoom & Focus
- IR LED: 24pcs Mini Array IR LED
- IR Range:30M

Specification					
Model no	TMT-4608	TMT-4605	TMT-4604	TMT-4603	TMT-7064
Camera Type	AHD (Analog High Definition Camera				
Effective Pixels	4K/8.0 Mega Pixels	5.0 Mega Pixels	4.0 Mega Pixels	3.0 Mega Pixels	2.0 Mega Pixels
Image Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor
Min. Illumination	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2
	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2
On Screen Display	Yes				
OSD Function	Manual/DC Lens, Shutter/AGC/WB,Pict Adjust,Mirror,Day /Night,DNR,BLC/HLC,Motion Detect, Privacy Zone				
IR Cut Filter	IR LED synchronous switching double filter				
Lens Mount	Auto Focus Variceal Lens 2.8-12mm				
Infrared Luminary	24pcs Mini Array IR LED				
Infrared Wavelength	850 nm				
Illuminate Distance	30 M				
Waterproof Criterion	IP66				
I/O Connector	1*DC Power Connector ,1* BNC Video Connector				
Supplied Voltage	DC12V				
Power Consumption	IR On: 600mA max., IR Off: Less than 200mA				
Work. Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)				
Weight	1.0 kg				

ORDERING INFORMATION		
Model No	Product ID	Description
TMT-7064	TMT-02ALA40BF	2MP AHD Auto Focus Varifocal Fixed IR Bullet Camera
TMT-4603	TMT-03ALA40BF	3MP AHD Auto Focus Varifocal Fixed IR Bullet Camera
TMT-4604	TMT-04ALA40BF	4MP AHD Auto Focus Varifocal Fixed IR Bullet Camera
TMT-4605	TMT-05ALA40BF	5MP AHD Auto Focus Varifocal Fixed IR Bullet Camera
TMT-4608	TMT-08ALA40BF	8MP AHD Auto Focus Varifocal Fixed IR Bullet Camera



8MP Network Auto Focus Verifocal Fixed IR Bullet Camera





TMT GLOBAL 4K/8MP Auto Focus IP Camera
 motorized lens 2.8-12mm Auto focus Bullet Camera

Feature

- Embedded Linux System
- H.264,H.265 Video Compression,
- Resolution 3840*2160
- Motorized Lens (Auto Focus) 2-12mm
- IP66 Rating indoor/outdoor

Specification				
Camera Type	Bullet IP Camera			
System	Embedded RTOS design			
Camera	Effective Pixels	4K/8 Mega Pixels	Main stream:3840*2160	Sub stream:1280*720
	Frames Rates	PAL:25fps(3840*2160)	NTSC:30fps(3840*2160)	
	Image Sensor	1/2.8" SONY IMX415 CMOS Sensor	8megapixel resolution (3864H*2202V)	
	DSP	Dual core 32-bit DSP	(Hi3516A)	
	Min. Illumination	Color 0.001Lux@F1.2	B/W 0.0001 Lux@F1.2	
	Adjust Parameters	DWDR, BLC,DNR,AE,AGC,D & N, Mirror, Flip, etc.		
Video	Compression	H.265/H.264 Main profile	Stream	support dual stream, AVI format
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable	Frame Rates	support 1~30fps adjust
Audio	Input and output	1ch input(micro phone),1ch output(Speaker & micro phone) Optional		
	Compression	G.711 compression, support two-way audio intercom, support audio and video synchronized output		
Alarm	Types	Motion Detection, Video Blind , Video Loss		
Network	WEB Browser	Support WEB remote config.(IE, Safari, Google Chrome, Firefox etc.)		
	Smart Phone	mobile remote Monitoring (iPhone, Android,....)		
	CMS Software	Uniform CMS Software(multiple devices management system)		
	Cloud P2P	www.tmtglobal.co.uk .TMTEYE platform		
	Network	1x RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP		
General	ONVIF	Support (ONVIF 2.6)	POE	Support(optional)
	Language	20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, and Turkish		
	IR Cut Filter	Set of double light switch IR-CUT filter	Lens Mount	4X Motorized Zoom Auto Focus 2.8-12mm Lens
	Infrared Luminary	24 pcs IR LED	Infrared Wavelength	850nm
	Illuminate Distance	25m	Waterproof Criterion	IP 66
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)	Supplied Voltage	DC12V/POE(802.3af/820.3at)
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA		
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)		
	Weight	0.6kg		

Ordering Information		
Model	Product code	Description
TMT-4008	TMT-08NLA40BF	8MP Network Auto Focus Verifocal Fixed IR Bullet Camera

2MP Network Auto Focus Verifocal Fixed IR Bullet Camera





TMT GLOBAL 2 MP Auto Focus IP Camera motorized lens 2.8-12mm Auto focus Bullet Camera

Feature

- Embedded Linux System
- H.264,H.265 Video Compression,
- Full HD Resolution 1920*1080
- Motorized Lens (Auto Focus) 2-12mm
- IP66 Rating indoor/outdoor

Specification				
Camera Type	Bullet IP Camera			
System	Embedded RTOS design			
Camera	Effective Pixels	2.0 Mega pixels	Main stream:1920*1080;1280*720	Sub stream:704*576
	Frames Rates	PAL:25fps(1920*1080)/(1280*720)	NTSC:30fps(1920*1080)/(1280*720)	
	Image Sensor	1/2.8" SONY IMX322 CMOS Sensor	2.13 megapixel resolution (1945H*1097V)	
	DSP	Dual core 32-bit DSP	(Hi3516C)	
	Min. Illumination	Color 0.01Lux@F1.2	B/W 0.001 Lux@F1.2	
	Adjust Parameters	DWDR, BLC,DNR,AE,AGC,D & N,Mirror,Flip,etc.		
Video	Compression	H.265/H.264 Main profile	Stream	support dual stream, AVI format
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable	Frame Rates	support 1~30fps adjust
Audio	Input and output	1ch input(micro phone),1ch output(Speaker & micro phone) Optional		
	Compression	G.711 compression, support two-way audio intercom, support audio and video synchronized output		
Alarm	Types	Motion Detection, Video Blind , Video Loss		
Network	WEB Browser	Support WEB remote config.(IE, Safari, Google Chrome, Firefox etc.)		
	Smart Phone	mobile remote Monitoring (iPhone, Android,....)		
	CMS Software	Uniform CMS Software(multiple devices management system)		
	Cloud P2P	www.tmtglobal.co.uk . TMTEYE platform		
	Network	1x RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP		
General	ONVIF	Support (ONVIF 2.6)	POE	Support(optional)
	Language	20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, and Turkish		
	IR Cut Filter	Set of double light switch IR-CUT filter	Lens Mount	4X Motorized Zoom Auto Focus 2.8-12mm Lens
	Infrared Luminary	4 pcs Array IR LED	Infrared Wavelength	850nm
	Illuminate Distance	40m	Waterproof Criterion	IP 66
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)	Supplied Voltage	DC12V/POE(802.3af/820.3at)
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA		
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)		
	Weight	0.6kg		

Ordering Information		
Model	Product code	Description
TMT-4012	TMT-02NLA41BF	2MP Network Auto Focus Verifocal Fixed IR Bullet Camera

3MP Network Auto Focus Verifocal Fixed IR Bullet Camera





TMT GLOBAL 3 MP Auto Focus IP Camera motorized lens 2.8-12mm Auto focus Bullet Camera

Feature

- Embedded Linux System
- H.264,H.265 Video Compression,
- Resolution 2046*1536
- Motorized Lens (Auto Focus) 2-12mm
- IP66 Rating indoor/outdoor

Specification

Camera Type		Bullet IP Camera			
System		Embedded RTOS design			
Camera	Effective Pixels	3.0 Mega pixels	Main stream:2046*1536	Sub stream:704*576	
	Frames Rates	PAL:25fps(2046*1536)	NTSC:30fps(2046*1536)		
	Image Sensor	1/2.8" SONY APTINA CMOS Sensor	3 megapixel resolution (2046H*1536V)		
	DSP	Dual core 32-bit DSP	(Hi3516C)		
	Min. Illumination	Color 0.01Lux@F1.2	B/W 0.001 Lux@F1.2		
	Adjust Parameters	DWDR, BLC,DNR,AE,AGC,D & N,Mirror,Flip,etc.			
Video	Compression	H.265/H.264 Main profile	Stream	support dual stream, AVI format	
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable	Frame Rates	support 1~30fps adjust	
Audio	Input and output	1ch input(micro phone),1ch output(Speaker & micro phone) Optional			
	Compression	G.711 compression, support two-way audio intercom, support audio and video synchronized output			
Alarm	Types	Motion Detection, Video Blind , Video Loss			
Network	WEB Browser	Support WEB remote config.(IE, Safari, Google Chrome, Firefox etc.)			
	Smart Phone	mobile remote Monitoring (iPhone, Android,....)			
	CMS Software	Uniform CMS Software(multiple devices management system)			
	Cloud P2P	www.tmtglobal.co.uk .TMTEYE platform			
	Network	1x RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP			
General	ONVIF	Support (ONVIF 2.6)	POE	Support(optional)	
	Language	20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, and Turkish			
	IR Cut Filter	Set of double light switch IR-CUT filter	Lens Mount	4X Motorized Zoom Auto Focus 2.8-12mm Lens	
	Infrared Luminary	4 pcs Array IR LED	Infrared Wavelength	850nm	
	Illuminate Distance	40m	Waterproof Criterion	IP 66	
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)	Supplied Voltage	DC12V/POE(802.3af/820.3at)	
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA			
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)			
	Weight	0.6kg			

Ordering Information

Model	Product code	Description
TMT-4013	TMT-03NLA41BF	3MP Network Auto Focus Verifocal Fixed IR Bullet Camera

4MP Network Auto Focus Verifocal Fixed IR Bullet Camera





TMT GLOBAL 4MP Auto Focus IP Camera motorized lens 2.8-12mm Auto focus Bullet Camera

Feature

- Embedded Linux System
- H.264,H.265 Video Compression,
- Resolution 2592*1520
- Motorized Lens (Auto Focus) 2-12mm
- IP66 Rating indoor/outdoor

Specification

Camera Type		Bullet IP Camera			
System		Embedded RTOS design			
Camera	Effective Pixels	4.0 Mega Pixels	Main stream:2592*1520	Sub stream:704*576	
	Frames Rates	PAL:25fps(2592*1520)	NTSC:30fps(2592*1520)		
	Image Sensor	1/3" OV4689 CMOS Sensor	4 megapixel resolution (2688H*1520V)		
	DSP	Dual core 32-bit DSP	(HI3516D)		
	Min. Illumination	Color 0.001Lux@F1.2	B/W 0.0001 Lux@F1.2		
	Adjust Parameters	DWDR, BLC,DNR,AE,AGC,D & N, Mirror, Flip, etc.			
Video	Compression	H.265/H.264 Main profile	Stream	support dual stream, AVI format	
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable	Frame Rates	support 1~30fps adjust	
Audio	Input and output	1ch input(micro phone),1ch output(Speaker & micro phone) Optional			
	Compression	G.711 compression, support two-way audio intercom, support audio and video synchronized output			
Alarm	Types	Motion Detection, Video Blind , Video Loss			
Network	WEB Browser	Support WEB remote config.(IE, Safari, Google Chrome, Firefox etc.)			
	Smart Phone	mobile remote Monitoring (iPhone, Android,....)			
	CMS Software	Uniform CMS Software(multiple devices management system)			
	Cloud P2P	www.tmtglobal.co.uk . TMTEYE platform			
	Network	1x RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP			
General	ONVIF	Support (ONVIF 2.6)	POE	Support(optional)	
	Language	20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, and Turkish			
	IR Cut Filter	Set of double light switch IR-CUT filter	Lens Mount	4X Motorized Zoom Auto Focus 2.8-12mm Lens	
	Infrared Luminary	4 pcs Array IR LED	Infrared Wavelength	850nm	
	Illuminate Distance	40m	Waterproof Criterion	IP 66	
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)	Supplied Voltage	DC12V/POE(802.3af/820.3at)	
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA			
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)			
	Weight	0.6kg			

Ordering Information

Model	Product code	Description
TMT-4014	TMT-04NLA41BF	4MP Network Auto Focus Verifocal Fixed IR Bullet Camera

8MP Network Auto Focus Verifocal Fixed IR Bullet Camera





TMT GLOBAL 4k/8 MP Auto Focus IP Camera motorized lens 2.8-12mm Auto focus Bullet Camera

Feature

- Embedded Linux System
- H.264,H.265 Video Compression,
- Resolution 3840*2160
- Motorized Lens (Auto Focus) 2-12mm
- IP66 Rating indoor/outdoor

Specification

Camera Type		Bullet IP Camera			
System		Embedded RTOS design			
Camera	Effective Pixels	4K/8 Mega Pixels	Main stream:3840*2160	Sub stream:1280*720	
	Frames Rates	PAL:25fps(3840*2160)	NTSC:30fps(3840*2160)		
	Image Sensor	1/2.8" SONY IMX415 CMOS Sensor	8megapixel resolution (3864H*2202V)		
	DSP	Dual core 32-bit DSP	(Hi3516A)		
	Min. Illumination	Color 0.001Lux@F1.2	B/W 0.0001 Lux@F1.2		
	Adjust Parameters	DWDR, BLC,DNR,AE,AGC,D & N, Mirror, Flip, etc.			
Video	Compression	H.265/H.264 Main profile	Stream	support dual stream, AVI format	
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable	Frame Rates	support 1~30fps adjust	
Audio	Input and output	1ch input(micro phone),1ch output(Speaker & micro phone) Optional			
	Compression	G.711 compression, support two-way audio intercom, support audio and video synchronized output			
Alarm	Types	Motion Detection, Video Blind , Video Loss			
Network	WEB Browser	Support WEB remote config.(IE, Safari, Google Chrome, Firefox etc.)			
	Smart Phone	mobile remote Monitoring (iPhone, Android,....)			
	CMS Software	Uniform CMS Software(multiple devices management system)			
	Cloud P2P	www.tmtglobal.co.uk .TMTEYE platform			
	Network	1x RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP			
	ONVIF	Support (ONVIF 2.6)	POE	Support(optional)	
General	Language	20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, and Turkish			
	IR Cut Filter	Set of double light switch IR-CUT filter	Lens Mount	4X Motorized Zoom Auto Focus 2.8-12mm Lens	
	Infrared Luminary	4 pcs Array IR LED	Infrared Wavelength	850nm	
	Illuminate Distance	40m	Waterproof Criterion	IP 66	
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)	Supplied Voltage	DC12V/POE(802.3af/820.3at)	
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA			
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)			
	Weight	0.6kg			

Ordering Information

Model	Product code	Description
TMT-4018	TMT-08NLA41BF	8MP Network Auto Focus Verifocal Fixed IR Bullet Camera

2MP Network Fixed IR Bullet Camera





TMT GLOBAL 2MP Fixed 3.6mm Lens IP Bullet Camera

Feature

- Embedded Linux System
- H.264,H.265 Video Compression,
- Full HD Resolution 1920*1080
- Fixed Lens 3.6mm
- IP66 Rating indoor/outdoor

Specification				
Camera Type	Bullet IP Camera			
System	Embedded RTOS design			
Camera	Effective Pixels	2.0 Mega pixels	Main stream:1920*1080	Sub stream:704*576
	Frames Rates	PAL:25fps(1920*1080)	NTSC:30fps(1920*1080)	
	Image Sensor	1/2.8" SONY IMX322 CMOS Sensor	2.13 megapixel resolution (1945H*1097V)	
	DSP	Dual core 32-bit DSP	(Hi3516E)	
	Min. Illumination	Color 0.01Lux@F1.2	B/W 0.01 Lux@F1.2	
	Adjust Parameters	DWDR, BLC,DNR,AE,AGC,D & N,Mirror,Flip,etc.		
Video	Compression	H.265/H.264 Main profile	Stream	support dual stream, AVI format
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable	Frame Rates	support 1~30fps adjust
Audio	Input and output	1ch input(micro phone),1ch output(Speaker & micro phone) Optional		
	Compression	G.711 compression, support two-way audio intercom, support audio and video synchronized output		
Alarm	Types	Motion Detection, Video Blind , Video Loss		
Network	WEB Browser	Support WEB remote config.(IE, Safari, Google Chrome, Firefox etc.)		
	Smart Phone	mobile remote Monitoring (iPhone, Android,...)		
	CMS Software	Uniform CMS Software(multiple devices management system)		
	Cloud P2P	www.tmtglobal.co.uk .TMTEYE platform		
	Network	1x RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP		
General	ONVIF	Support (ONVIF 2.6)	POE	Support(optional)
	Language	20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, and Turkish		
	IR Cut Filter	Set of double light switch IR-CUT filter	Lens Mount	Fixed Lens 3.6mm/F2.0
	Infrared Luminary	2pcs SMD LED	Infrared Wavelength	850nm
	Illuminate Distance	40m	Waterproof Criterion	IP 66
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)	Supplied Voltage	DC12V/POE(802.3af/820.3at)
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA		
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)		
	Weight	0.6kg		

Ordering Information		
Model	Product code	Description
TMT-4062	TMT-02NLF43BF	2MP Network Fixed IR Bullet Camera

3MP Network Fixed IR Bullet Camera





TMT GLOBAL 3MP Fixed 3.6mm Lens IP Bullet Camera

Feature

- Embedded Linux System
- H.264,H.265 Video Compression,
- Resolution 2046*1536
- Fixed Lens 3.6mm
- IP66 Rating indoor/outdoor

Specification

Camera Type		Bullet IP Camera			
System		Embedded RTOS design			
Camera	Effective Pixels	3.0 Mega pixels	Main stream:2046*1536	Sub stream:704*576	
	Frames Rates	PAL:25fps(2046*1536)	NTSC:30fps(2046*1536)		
	Image Sensor	1/2.8" SONY APTINA CMOS Sensor		3 megapixel resolution (2046H*1536V)	
	DSP	Dual core 32-bit DSP		(Hi3516C)	
	Min. Illumination	Color 0.01Lux@F1.2		B/W 0.001 Lux@F1.2	
	Adjust Parameters	DWDR, BLC,DNR,AE,AGC,D & N,Mirror,Flip,etc .			
Video	Compression	H.265/H.264 Main profile		Stream	support dual stream, AVI format
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable		Frame Rates	support 1~30fps adjust
Audio	Input and output	1ch input(micro phone),1ch output(Speaker & micro phone) Optional			
	Compression	G.711 compression, support two-way audio intercom, support audio and video synchronized output			
Alarm	Types	Motion Detection, Video Blind , Video Loss			
Network	WEB Browser	Support WEB remote config.(IE, Safari, Google Chrome, Firefox etc.)			
	Smart Phone	mobile remote Monitoring (iPhone, Android,....)			
	CMS Software	Uniform CMS Software(multiple devices management system)			
	Cloud P2P	www.tmtglobal.co.uk . TMTEYE platform			
	Network	1x RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP			
	ONVIF	Support (ONVIF 2.6)	POE	Support(optional)	
General	Language	20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, and Turkish			
	IR Cut Filter	Set of double light switch IR-CUT filter	Lens Mount	Fixed Lens 3.6mm/F2.0	
	Infrared Luminary	2pcs SMD LED	Infrared Wavelength	850nm	
	Illuminate Distance	40m	Waterproof Criterion	IP 66	
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)	Supplied Voltage	DC12V/POE(802.3af/820.3at)	
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA			
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)			
	Weight	0.6kg			

Ordering Information

Model	Product code	Description
TMT-4063	TMT-03NLF43BF	3MP Network Fixed IR Bullet Camera

AHD Auto Focus Verifocal Fixed IR Bullet Camera





**TMT GLOBAL 2,3,4,5,4K/8 MP Auto Focus motorized lens
2.8-12mm Auto focus AHD Bullet Camera**

Features

- Waterproof Bullet Camera
- 3-axis Adjustable Bracket
- Lens: Auto focus Varifocal 2.8-12mm
- Adjustable Zoom & Focus
- IR LED: 24pcs Mini Array IR LED
- IR Range:30M

Specification					
Model no	TMT-4618	TMT-4615	TMT-4614	TMT-4613	TMT-4612
Camera Type	AHD (Analog High Definition Camera)				
Effective Pixels	4K/8.0 Mega Pixels	5.0 Mega Pixels	4.0 Mega Pixels	3.0 Mega Pixels	2.0 Mega Pixels
Image Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor
Min. Illumination	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2
	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2
On Screen Display	Yes				
OSD Function	Manual/DC Lens, Shutter/AGC/WB,Pict Adjust,Mirror,Day/Night,DNR,BLC/HLC,Motion Detect, Privacy Zone				
IR Cut Filter	IR LED synchronous switching double filter				
Lens Mount	Auto Focus Variceal Lens 2.8-12mm				
Infrared Luminary	24pcs Mini Array IR LED				
Infrared Wavelength	850 nm				
Illuminate Distance	30 M				
Waterproof Criterion	IP66				
I/O Connector	1*DC Power Connector ,1* BNC Video Connector				
Supplied Voltage	DC12V				
Power Consumption	IR On: 600mA max., IR Off: Less than 200mA				
Work. Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)				
Weight	1.0 kg				

ORDERING INFORMATION		
Model No	Product ID	Description
TMT-4612	TMT-02ALA41BF	2MP AHD Auto Focus Verifocal Fixed IR Bullet Camera
TMT-4613	TMT-03ALA41BF	3MP AHD Auto Focus Verifocal Fixed IR Bullet Camera
TMT-4614	TMT-04ALA41BF	4MP AHD Auto Focus Verifocal Fixed IR Bullet Camera
TMT-4615	TMT-05ALA41BF	5MP AHD Auto Focus Verifocal Fixed IR Bullet Camera
TMT-4618	TMT-08ALA41BF	8MP AHD Auto Focus Varifocal Fixed IR Bullet Camera

AHD Auto Focus Verifocal Fixed IR Bullet Camera





**TMT GLOBAL 2,3,4,5,4K/8 MP Auto Focus motorized lens
2.8-12mm Auto focus AHD Bullet Camera**

Features

- Waterproof Bullet Camera
- 3-axis Adjustable Bracket
- Lens: Auto focus Varifocal 2.8-12mm
- Adjustable Zoom & Focus
- IR LED: 24pcs Mini Array IR LED
- IR Range:30M

Specification					
Model no	TMT-4628	TMT-4625	TMT-4624	TMT-4623	TMT-4622
Camera Type	AHD (Analog High Definition Camera)				
Effective Pixels	4K/8.0 Mega Pixels	5.0 Mega Pixels	4.0 Mega Pixels	3.0 Mega Pixels	2.0 Mega Pixels
Image Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor
Min. Illumination	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2
	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2
On Screen Display	Yes				
OSD Function	Manual/DC Lens, Shutter/AGC/WB,Pict Adjust,Mirror,Day /Night,DNR,BLC/HLC,Motion Detect, Privacy Zone				
IR Cut Filter	IR LED synchronous switching double filter				
Lens Mount	Auto Focus Variceal Lens 2.8-12mm				
Infrared Luminary	24pcs Mini Array IR LED				
Infrared Wavelength	850 nm				
Illuminate Distance	30 M				
Waterproof Criterion	IP66				
I/O Connector	1*DC Power Connector ,1* BNC Video Connector				
Supplied Voltage	DC12V				
Power Consumption	IR On: 600mA max., IR Off: Less than 200mA				
Work. Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)				
Weight	1.0 kg				

ORDERING INFORMATION		
Model No	Product ID	Description
TMT-4622	TMT-02ALA42BF	2MP AHD Auto Focus Verifocal Fixed IR Bullet Camera
TMT-4623	TMT-03ALA42BF	3MP AHD Auto Focus Verifocal Fixed IR Bullet Camera
TMT-4624	TMT-04ALA42BF	4MP AHD Auto Focus Verifocal Fixed IR Bullet Camera
TMT-4625	TMT-05ALA42BF	5MP AHD Auto Focus Verifocal Fixed IR Bullet Camera
TMT-4628	TMT-08ALA42BF	8MP AHD Auto Focus Varifocal Fixed IR Bullet Camera

AHD Fixed IR Bullet Camera





TMT GLOBAL 2,3,4,5,4K/8 MP Fixed lens 3.6mm AHD Bullet Camera

Features

- Waterproof Bullet Camera
- 3-axis Adjustable Bracket
- Lens: Fixed 3.6mm
- IR LED: 24pcs Mini Array IR LED
- IR Range:30M

Specification					
Model no	TMT-4638	TMT-4635	TMT-4634	TMT-4633	TMT-4632
Camera Type	AHD (Analog High Definition Camera)				
Effective Pixels	4K/8.0 Mega Pixels	5.0 Mega Pixels	4.0 Mega Pixels	3.0 Mega Pixels	2.0 Mega Pixels
Image Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor
Min. Illumination	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2
	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2
On Screen Display	Yes				
OSD Function	Manual/DC Lens, Shutter/AGC/WB,Pict Adjust,Mirror,Day/Night,DNR,BLC/HLC,Motion Detect, Privacy Zone				
IR Cut Filter	IR LED synchronous switching double filter				
Lens Mount	Fixed Lens				
Infrared Luminary	24pcs Mini Array IR LED				
Infrared Wavelength	850 nm				
Illuminate Distance	30 M				
Waterproof Criterion	IP66				
I/O Connector	1*DC Power Connector ,1* BNC Video Connector				
Supplied Voltage	DC12V				
Power Consumption	IR On: 600mA max., IR Off: Less than 200mA				
Work. Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)				
Weight	1.0 kg				

ORDERING INFORMATION		
Model No	Product ID	Description
TMT-4632	TMT-02ALF43BF	2MP AHD Fixed IR Bullet Camera
TMT-4633	TMT-03ALF43BF	3MP AHD Fixed IR Bullet Camera
TMT-4634	TMT-04ALF43BF	4MP AHD Fixed IR Bullet Camera
TMT-4635	TMT-05ALF43BF	5MP AHD Fixed IR Bullet Camera
TMT-4638	TMT-08ALF43BF	8MP AHD Fixed IR Bullet Camera

AHD Fixed IR Bullet Camera





**TMT GLOBAL 2,3,4,5,4K/8 MP Fixed lens
3.6mm AHD Bullet Camera**

Features

- Waterproof Bullet Camera
- 3-axis Adjustable Bracket
- Lens: Fixed 3.6mm
- IR LED: 24pcs Mini Array IR LED
- IR Range:30M

Specification					
Model no	TMT-4648	TMT-4645	TMT-4644	TMT-4643	TMT-4642
Camera Type	AHD (Analog High Definition Camera)				
Effective Pixels	4K/8.0 Mega Pixels	5.0 Mega Pixels	4.0 Mega Pixels	3.0 Mega Pixels	2.0 Mega Pixels
Image Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor	1/2.8" SONY CMOS Sensor
Min. Illumination	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2
	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2	B/W 0.01 Lux@F1.2
On Screen Display	Yes				
OSD Function	Manual/DC Lens, Shutter/AGC/WB,Pict Adjust,Mirror,Day/Night,DNR,BLC/HLC,Motion Detect, Privacy Zone				
IR Cut Filter	IR LED synchronous switching double filter				
Lens Mount	Fixed Lens				
Infrared Luminary	24pcs Mini Array IR LED				
Infrared Wavelength	850 nm				
Illuminate Distance	30 M				
Waterproof Criterion	IP66				
I/O Connector	1*DC Power Connector ,1* BNC Video Connector				
Supplied Voltage	DC12V				
Power Consumption	IR On: 600mA max., IR Off: Less than 200mA				
Work. Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)				
Weight	1.0 kg				

ORDERING INFORMATION		
Model No	Product ID	Description
TMT-4642	TMT-02ALF44BF	2MP AHD Fixed IR Bullet Camera
TMT-4643	TMT-03ALF44BF	3MP AHD Fixed IR Bullet Camera
TMT-4644	TMT-04ALF44BF	4MP AHD Fixed IR Bullet Camera
TMT-4645	TMT-05ALF44BF	5MP AHD Fixed IR Bullet Camera
TMT-4648	TMT-08ALF44BF	8MP AHD Fixed IR Bullet Camera