

FIBER PATCH PANEL SC/APC SIMPLEX **ADAPTER**



















www.tmtuae.com | info@tmtuae.com





TMT GLOBAL 19" Rack Mounted Optical Fiber Patch Panels 12,24 Port SM,DX Adapters

Features	Applications	
 Sliding patch panel for easy rework and maintenance Front Panel equipped with SC,LC ,FC, Adaptors Connection Point to fix Fiber Cassette cold rolled steel Constructional Structure Fixed Splice tray 	☐ Telecommunication networks ☐ FTTH ☐ LAN, WAN, CATV networks ☐ Active device termination ☐ CCTV ☐ IPTV	

Specification		
ELEMENT	12/24 Port	
Mounting Type	Rack	
Rack Type	Slide	
U Size	1U (44 mm)	
Width	483mm	
Depth	230mm	
Weight	2.4kgs fully	
Packaged Dimensions	483mm W X 44mm H x 230mm D	
IP Rating	P20	
Adapter Options	SC /LC /FC	
Number of ports	24	
Cable Entry 20mm	2	
Mounting adjustment range	50mm	
Material	Cold Rolled Steel	
Material thickness	1.2mm	
Material coating	Powder coating	
Color	Black/white	
Operating Temperature	-40°c to + 50°c	
Compliant to	RoHS, Reach / SVHC	
Designed in accordance	TIA/EIA 568.C, ISO/IEC 11801, EN 50173,IEC 60304, IEC 61754, EN 297-1	

Model No	Product ID	Ordering Information
TMT-3301	TMT-242SASL	24 PORT SLIDING TYPE FIBER PATCH PANEL WITH SC/APC SIMPLEX ADAPTER













