

FIBER PATCH PANEL LC/UPC DUPLEX ADAPTER





TMT GLOBAL 19" Rack Mounted Optical Fiber Patch Panels 12,24,48 Port SM,DX Adapters

Features

- Sliding patch panel for easy rework and maintenance
- Front Panel equipped with SC,LC,FC, Adaptors
- Connection Point to fix Fiber Cassette
- cold rolled steel Constructional Structure
- Fixed Splice tray

Applications

- Telecommunication networks
- FTTH
- LAN, WAN, CATV networks
- Active device termination
- CCTV
- IPTV

Specification	
ELEMENT	12/24/48 Port
Mounting Type	Rack
Rack Type	Slide
U Size	1U (44 mm)
Width	483mm
Depth	230mm
Weight	2.4kgs fully
Packaged Dimensions	483mm W X 44mm H x 230mm D
IP Rating	P20
Adapter Options	SC /LC /FC
Number of ports	48
Cable Entry 20mm	2
Mounting adjustment range	50mm
Material	Cold Rolled Steel
Material thickness	1.2mm
Material coating	Powder coating
Color	Black/white
Operating Temperature	-40°c to + 50°c
Compliant to	RoHS, Reach / SVHC
Designed in accordance	TIA/EIA 568.C, ISO/IEC 11801, EN 50173,IEC 60304, IEC 61754, EN 297-1

Model No	Product ID	Ordering Information
TMT-3323	TMT-482LUDL	48 PORT SLIDING TYPE FIBER PATCH PANEL WITH LC/UPC DUPLEX ADAPTER