



5MP NETWORK AUTO FOCUS VARIFOCAL FIXED IR BULLET CAMERA





TMT GLOBAL 5MP Auto Focus IP Camera motorized lens 2.8-12mm Auto focus Bullet Camera

Feature

- Embedded Linux System
- H.264,H.265 Video Compression,
- Resolution 2592*1944
- Motorized Lens (Auto Focus) 2-12mm
- IP66 Rating indoor/outdoor

Specification				
Camera Type	Bullet IP Camera			
System	Embedded RTOS design			
Camera	Effective Pixels	5 Mega Pixels	Main stream:2592*1944	Sub stream:704*576
	Frames Rates	PAL:25fps(2592*1944)	NTSC:30fps(2592*1944)	
	Image Sensor	1/2.8" SONY IMX335CMOS Sensor	5megapixel resolution (2592*1944V)	
	DSP	Dual core 32-bit DSP	(Hi3516E)	
	Min. Illumination	Color 0.01Lux@F1.2	B/W 0.01 Lux@F1.2	
	Adjust Parameters	DWDR, BLC,DNR,AE,AGC,D & N, Mirror, Flip, etc .		
Video	Compression	H.265/H.264 Main profile	Stream	support dual stream, AVI format
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable	Frame Rates	support 1~30fps adjust
Audio	Input and output	1ch input(micro phone),1ch output(Speaker & micro phone) Optional		
	Compression	G.711 compression, support two-way audio intercom, support audio and video synchronized output		
Alarm	Types	Motion Detection, Video Blind , Video Loss		
Network	WEB Browser	Support WEB remote config.(IE, Safari, Google Chrome, Firefox etc.)		
	Smart Phone	mobile remote Monitoring (iPhone, Android,....)		
	CMS Software	Uniform CMS Software(multiple devices management system)		
	Cloud P2P	www.tmtglobal.co.uk .TMTEYE platform		
	Network	1x RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP		
General	ONVIF	Support (ONVIF 2.4)	POE	Support(optional)
	Language	20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, and Turkish		
	IR Cut Filter	Set of double light switch IR-CUT filter	Lens Mount	4X Motorized Zoom Auto Focus 2.8-12mm Lens
	Infrared Luminary	24pcs SMD LED	Infrared Wavelength	850nm
	Illuminate Distance	25m	Waterproof Criterion	IP 66
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)	Supplied Voltage	DC12V/POE(802.3af/820.3at)
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA		
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°)		
	Weight	0.6kg		

Ordering Information		
Model	Product code	Description
TMT-4005	TMT-05NLA40BF	5MP Network Auto Focus Varifocal Fixed IR Bullet Camera