

16CH STAND ALONE POE NVR





TMT Global 16Ch 4K NVR H.265 With 16Port POE Output Support 5MP Main Stream Preview And Playback

Feature:

- H.265 16CH 5MP 1U NVR
- Support TMTEYE P2P cloud services
- Provide networked centralized monitoring and management software
- Support 265/H.264 coding front end adaptive access
- Support ONVIF, High profile S and High profile G

Product highlights

Support H.265+/H.265/H.264 coding front end adaptive access.

Support ONVIF, High profile S, High profile G, and can be connected to network cameras that comply with ONVIF, RTSP standards made by many major manufacturers.

Support IPC front-end Intelligence: target count, object left/lost, area detection, line crossing.

Support TMTEYE P2P cloud services, through cloud access, cloud monitoring, cloud forwarding to achieve any terminal access to NVR anytime, anywhere.

Support immediate playback function under preview screen without affecting other channel preview.

Support for adaptive bit stream preview and playback 4 screen maximum support 1920*1080, single screen 3840*2160.

Provide networked centralized monitoring and management software.

Specification				
Operating System		Embedded LINUX operating system		
Video Standard		H.265 +/- H.265 /H.264		
Intelligent Support	IPC support	With its own TMT Global intelligent IPC: target count, object left/lost, area detection, line crossing With its own TMT Global intelligent IPC: target count, object left/lost, area detection, line -crossing , sound detection, fire detection, video diagnostic detection.		
	Video & Audio Input	Video Input	16 digital (3840*2160) + 16 Preview + 16 Playback , 16ch 4K or below channel IPC	
Video & Audio Output	Preview Split	Bandwidth	80MB	
		VGA Output	1ch	
		HDMI Output	1ch , HDMI can output audio at the same time Note : 16ch, input 4K resolution	
Video & Audio Coding	Video Resolution	4K/5MP/4MP/3MP/1080P and below resolution	Synchronized Playback	4ch
External Port	Internet Port	1x, RJ45 10M/100M adaptive Ethernet port	USB Port	2xUSB2.0, Front 1x , Rear 1x
HDD	HDD Port	2xSATA	MAX Capacity	Single port up to 8TB
POE	Port	8x independent 10/100Mbps Ethernet port , support 200M network cable	Support Standard	IEEE802.3af
P2P Remote Monitoring	TMTEYE	Supports iPhone, iPad, Android Smart phone		
		Supports Windows 7 and above computer client, supports Apple MAC computer client		
Power Supply		DC 52V 4.62A		
Working Temperature		-10? --+ 55?		
Working Humidity		10% -90%		
Power Consumption (no HDD)		POE=208 W , NVR main board =8 W		
Dimensions		Device : 350mmx240mmx68mm, Packing : 409mmx365mmx129m		
Weight (Without HDD)		N.W. : 2Kg; Packing : 3.5Kg		

Ordering Information		
Model	Product code	Description
TMT-4916	TMT-SP16118	16ch stand alone poe nvr