

MAGNETIC SINGLE DOOR LOCK SERIES





280KG Single Door Magnetic Lock (Door status signal out putt)

The **TMT GLOBAL** Electromagnetic lock is using the leading production equipment and packaging technology of the international. Produced the electromagnetic lock is not only higher than similar products by more than 20% of the lock holding force, but also the antioxidant capacity of the surface of magnetic lock is reached the international advanced level. Which are widely used in airports, subways, banks, prisons, intelligent buildings.

- Heavy duty Structure
- Ultra Plus sensitive
- Low Consumption
- High Strength Aluminum Alloy Materials
- Pure Copper Magnetic Coil
- Silicon Steel Sheet Main Materials
- NO/NC Signal
- Red/ Green Indicator
- Delay Adjustment
- 12/24v Adjustable

Specification	
Lock Size	170Lx35Wx21H(mm)
Armature plate	130Lx33Wx9.3H(mm)
Holding Force	280kg(350Lbs)
Voltage	DC12V or DC24V (adjustable)
Current Draw	12V/500mA 24V/250mA
Signal Output	Dry Contact, Max Rating of Contact Current 3A
Suitable for	Wooden door , Glass door ,Metal door , Fireproof door
Surface Temp	≤+20°C
Operating Temp	-10~+55°C(14-131F)
Suitable Humidity	0~90%(non-condensing)
Finishes for Shell	Anodized aluminium surface texture processing
Finishes for Magnetic	Zinc
Finishes for Armature	Zinc
Weight	1.1kg

ORDER INFORMATION	
Model No	Description
TMT-7646	280KG SINGLE DOOR MAGNETIC DOOR LOCK