




PRODUCT & CONSTRUCTION

TMT-DS-5X14ZMPX | REV 00 | PAGE 1 OF 2



CAT5E U/UTP 24 AWG 4-PAIR PVC NETWORK CABLE – 305 M

CAT5e | U/UTP | 100 MHz | Indoor fixed installation

TMT Global CAT5e U/UTP network cable with 24 AWG TMT Copper conductors, HDPE insulation and a PVC jacket. Supplied in a 305 m pack for indoor fixed installation.

PHYSICAL AND MECHANICAL PROPERTIES

PROPERTY	DECLARED VALUE
Basic conductor	TMT Copper
Conductor size	24 AWG
Insulation	HDPE
Insulated conductors	8 conductors, twisted in 4 pairs
Pair colour code	Blue/White-Blue; Orange/White-Orange; Green/White-Green; Brown/White-Brown
Outer jacket	PVC compound
Standard jacket colours	10 approved colours
Standard surface marking	TMT Global P/N, cable description, metre mark and model number
Maximum pulling force	110 N
Minimum short-term bend radius	6 x OD
Storage temperature	-20 to +80 °C
Operating temperature	-20 to +60 °C
Installation temperature	0 to +50 °C
Flame propagation	IEC 60332-1-2

KEY DATA	APPLICATIONS	FLAME TEST
24 AWG 4 PAIRS PVC 305 m	Structured cabling LAN infrastructure CCTV AV and intercom	IEC 60332-1-2



ELECTRICAL SPECIFICATIONS

PARAMETER	DECLARED VALUE	PARAMETER	DECLARED VALUE
Characteristic impedance	100 ± 6 Ω @ 1–100 MHz	Dielectric strength	1,500 V / 1 minute min. RMS
DC resistance	93 Ω/km max.	Velocity of propagation (NVP)	67–69%
Resistance unbalance	2% max.	Propagation delay	534 + 36/√f ns/100 m max. @ 1–100 MHz
Mutual capacitance	5.6 nF/100 m max. @ 1 kHz	Propagation delay skew	35 ns/100 m max.
Capacitance unbalance	1,600 pF/m max. @ 1 kHz	Insulation resistance	5,000 MΩ·km min. @ 500 V DC
Voltage rating	72 V DC max.	Coupling attenuation	Not applicable (unscreened construction)

STANDARDS & DECLARED CLASSIFICATION

REFERENCE	APPLICATION
ANSI/TIA-568.2-D (manufacturer-declared reference)	Manufacturer-declared cabling reference
EN 50288-3-1	CAT5e U/UTP cable reference
IEC 61156-5:2020	Balanced communication cable
ISO/IEC 11801-1 (Class D)	Generic cabling classification
IEC 60332-1-2	Single insulated wire/cable flame propagation

ORDERING INFORMATION

ITEM CODE	JACKET	COLOUR	PACK
5X14ZMPB	PVC	Blue	305 m
5X14ZMPG	PVC	Grey	305 m
5X14ZMPK	PVC	Black	305 m
5X14ZMPN	PVC	Green	305 m
5X14ZMPO	PVC	Orange	305 m
5X14ZMPR	PVC	Red	305 m
5X14ZMPV	PVC	Violet	305 m
5X14ZMPW	PVC	White	305 m
5X14ZMPY	PVC	Yellow	305 m
5X14ZMPA	PVC	Aqua	305 m

PACKAGING: 305 m | COLOURS: 10 listed models