




## PRODUCT &amp; CONSTRUCTION

TMT-7401 | REV 00 | PAGE 1 OF 2



## CAT6 U/UTP SERIES

CAT6 U/UTP 23 AWG 4-PAIR PE  
OUTDOOR NETWORK CABLE – 305  
M

CAT6 | U/UTP | 250 MHz | Outdoor fixed installation

TMT Global CAT6 U/UTP network cable with 23 AWG Bare Copper conductors, HDPE insulation and a PE Outdoor jacket. Supplied in a 305 m pack for outdoor fixed installation.

## PHYSICAL AND MECHANICAL PROPERTIES

| PROPERTY                       | DECLARED VALUE                                                             |
|--------------------------------|----------------------------------------------------------------------------|
| Basic conductor                | Bare Copper                                                                |
| Conductor size                 | 23 AWG                                                                     |
| Insulation                     | HDPE                                                                       |
| Insulated conductors           | 8 conductors, twisted in 4 pairs                                           |
| Pair colour code               | Blue/White-Blue; Orange/White-Orange; Green/White-Green; Brown/White-Brown |
| Outer jacket                   | Heavy-duty, black, UV-resistant PE compound                                |
| Cable construction             | Unscreened construction with central pair divider                          |
| Standard surface marking       | TMT Global P/N, cable description, metre mark and model number             |
| Maximum pulling force          | 110 N                                                                      |
| Minimum short-term bend radius | 6 x OD                                                                     |
| Storage temperature            | -20 to +80 °C                                                              |
| Operating temperature          | -20 to +60 °C                                                              |
| Installation temperature       | 0 to +50 °C                                                                |
| Flame propagation              | IEC 60332-1-2                                                              |

## KEY DATA

23 AWG | 4 PAIRS | PE Outdoor | 305 m

## APPLICATIONS

Structured cabling | LAN infrastructure | CCTV | AV and intercom

## FLAME TEST

IEC 60332-1-2



ELECTRICAL SPECIFICATIONS

| PARAMETER                | DECLARED VALUE            | PARAMETER                     | DECLARED VALUE                           |
|--------------------------|---------------------------|-------------------------------|------------------------------------------|
| Characteristic impedance | 100 ± 6 Ω @ 1–250 MHz     | Dielectric strength           | 1,500 V / 1 minute min. RMS              |
| DC resistance            | 93 Ω/km max.              | Velocity of propagation (NVP) | 67–69%                                   |
| Resistance unbalance     | 2% max.                   | Propagation delay             | 534 + 36/√f ns/100 m max. @ 1–250 MHz    |
| Mutual capacitance       | 5.6 nF/100 m max. @ 1 kHz | Propagation delay skew        | 35 ns/100 m max.                         |
| Capacitance unbalance    | 1,600 pF/m max. @ 1 kHz   | Insulation resistance         | 5,000 MΩ·km min. @ 500 V DC              |
| Voltage rating           | 72 V DC max.              | Coupling attenuation          | Not applicable (unscreened construction) |

STANDARDS & DECLARED CLASSIFICATION

| REFERENCE                                          | APPLICATION                                   |
|----------------------------------------------------|-----------------------------------------------|
| ANSI/TIA-568.2-D (manufacturer-declared reference) | Manufacturer-declared cabling reference       |
| EN 50288-6-1                                       | CAT6 U/UTP cable reference                    |
| IEC 61156-5:2020                                   | Balanced communication cable                  |
| ISO/IEC 11801-1 (Class E)                          | Generic cabling classification                |
| IEC 60332-1-2                                      | Single insulated wire/cable flame propagation |

ORDERING INFORMATION

| ITEM CODE | JACKET     | COLOUR | PACK  |
|-----------|------------|--------|-------|
| 6X135BOK  | PE Outdoor | Black  | 305 m |

This construction is supplied in black with its specified outdoor jacket. Refer to the item code above when ordering.

PACKAGING: 305 m | COLOUR: Black only