




PRODUCT & CONSTRUCTION

TMT-7401 | REV 00 | PAGE 1 OF 2



CAT6 U/UTP SERIES

CAT6 U/UTP 23 AWG 4-PAIR PVC NETWORK CABLE – 305 M

CAT6 | U/UTP | 250 MHz | Indoor fixed installation

TMT Global CAT6 U/UTP network cable with 23 AWG Bare Copper conductors, HDPE insulation and a PVC jacket. Supplied in a 305 m pack for indoor fixed installation.

PHYSICAL AND MECHANICAL PROPERTIES

PROPERTY	Overall Coverage: Unshielded
Basic conductor	Bare Copper
Conductor size	23 AWG
Insulation	HDPE
Insulated conductors	8 conductors, twisted in 4 pairs
Pair colour code	Blue/White-Blue; Orange/White-Orange; Green/White-Green; Brown/White-Brown
Outer jacket	PVC compound
Cable construction	10 approved colours
Standard surface marking	TMT Global P/N, cable description, metre mark and model number
Maximum pulling force	110 N
Minimum short-term bend radius	6 x OD
Storage temperature	-20 to +80 °C
Operating temperature	-20 to +60 °C
Installation temperature	0 to +50 °C
Flame propagation	IEC 60332-1-2

KEY DATA 23 AWG 4 PAIRS PVC 305 m	APPLICATIONS Structured cabling LAN infrastructure CCTV AV and intercom	FLAME TEST IEC 60332-1-2
---	---	------------------------------------



ELECTRICAL SPECIFICATIONS

PARAMETER	DECLARED VALUE	PARAMETER	DECLARED VALUE
Characteristic impedance	100 ± 6 Ω @ 1–250 MHz	Dielectric strength	1,500 V / 1 minute min. RMS
DC resistance	93 Ω/km max.	Velocity of propagation (NVP)	67–69%
Resistance unbalance	2% max.	Propagation delay	534 + 36/√f ns/100 m max. @ 1–250 MHz
Mutual capacitance	5.6 nF/100 m max. @ 1 kHz	Propagation delay skew	35 ns/100 m max.
Capacitance unbalance	1,600 pF/m max. @ 1 kHz	Insulation resistance	5,000 MΩ·km min. @ 500 V DC
Voltage rating	72 V DC max.	Coupling attenuation	Not applicable (unscreened construction)

STANDARDS & DECLARED CLASSIFICATION

REFERENCE	APPLICATION
ANSI/TIA-568.2-D (manufacturer-declared reference)	Manufacturer-declared cabling reference
EN 50288-6-1	CAT6 U/UTP cable reference
IEC 61156-5:2020	Balanced communication cable
ISO/IEC 11801-1 (Class E)	Generic cabling classification
IEC 60332-1-2	Single insulated wire/cable flame propagation

ORDERING INFORMATION

ITEM CODE	JACKET	COLOUR	PACK
6X138BPB	PVC	Blue	305 m
6X138BPG	PVC	Grey	305 m
6X138BPK	PVC	Black	305 m
6X138BPN	PVC	Green	305 m
6X138BPO	PVC	Orange	305 m
6X138BPR	PVC	Red	305 m
6X138BPV	PVC	Violet	305 m
6X138BPW	PVC	White	305 m
6X138BPY	PVC	Yellow	305 m
6X138BPA	PVC	Aqua	305 m

PACKAGING: 305 m | COLOURS: 10 listed models