




PRODUCT & CONSTRUCTION

TMT-7401 | REV 00 | PAGE 1 OF 2



CAT6 S/FTP SERIES

CAT6 S/FTP 23 AWG 4-PAIR PVC NETWORK CABLE – 305 M

CAT6 | S/FTP | 250 MHz | Indoor fixed installation

TMT Global CAT6 S/FTP network cable with 23 AWG TMT Copper conductors, HDPE insulation and a PVC jacket. Supplied in a 305 m pack for indoor fixed installation.

PHYSICAL AND MECHANICAL PROPERTIES

PROPERTY	DECLARED VALUE
Basic conductor	TMT Copper
Conductor size	23 AWG
Insulation	HDPE
Insulated conductors	8 conductors, twisted in 4 pairs
Pair colour code	Blue/White-Blue; Orange/White-Orange; Green/White-Green; Brown/White-Brown
Outer jacket	PVC compound
Overall Coverage	Braiding Shield +Polyester-aluminum tape
Standard surface marking	TMT Global P/N, cable description, metre mark and model number
Maximum pulling force	110 N
Minimum short-term bend radius	8 x OD
Storage temperature	-20 to +80 °C
Operating temperature	-20 to +60 °C
Installation temperature	0 to +50 °C
Flame propagation	IEC 60332-1-2

KEY DATA

23 AWG | 4 PAIRS | PVC | 305 m

APPLICATIONS

Structured cabling | LAN infrastructure | CCTV | AV and intercom

FLAME TEST

IEC 60332-1-2



PERFORMANCE & ORDERING

TMT-7401 | REV 00 | PAGE 2 OF 2

ELECTRICAL SPECIFICATIONS

PARAMETER	DECLARED VALUE	PARAMETER	DECLARED VALUE
Characteristic impedance	100 ± 6 Ω @ 1–250 MHz	Dielectric strength	1,500 V / 1 minute min. RMS
DC resistance	93 Ω/km max.	Velocity of propagation (NVP)	67–69%
Resistance unbalance	2% max.	Propagation delay	534 + 36/√f ns/100 m max. @ 1–250 MHz
Mutual capacitance	5.6 nF/100 m max. @ 1 kHz	Propagation delay skew	35 ns/100 m max.
Capacitance unbalance	1,600 pF/m max. @ 1 kHz	Insulation resistance	5,000 MΩ·km min. @ 500 V DC
Voltage rating	72 V DC max.	Coupling attenuation	40 dB min. @ 30–100 MHz; 40–20 log(f/100) @ 100–250 MHz

STANDARDS & DECLARED CLASSIFICATION

REFERENCE	APPLICATION
ANSI/TIA-568.2-D (manufacturer-declared reference)	Manufacturer-declared cabling reference
EN 50288-5-1	CAT6 S/FTP cable reference
IEC 61156-5:2020	Balanced communication cable
ISO/IEC 11801-1 (Class E)	Generic cabling classification
IEC 60332-1-2	Single insulated wire/cable flame propagation

ORDERING INFORMATION

ITEM CODE	JACKET	COLOUR	PACK
6X536MPB	PVC	Blue	305 m
6X536MPG	PVC	Grey	305 m
6X536MPK	PVC	Black	305 m
6X536MPN	PVC	Green	305 m
6X536MPO	PVC	Orange	305 m
6X536MPR	PVC	Red	305 m
6X536MPV	PVC	Violet	305 m
6X536MPW	PVC	White	305 m
6X536MPY	PVC	Yellow	305 m
6X536MPA	PVC	Aqua	305 m

PACKAGING: 305 m | COLOURS: 10 listed models